

## SIM PANDA PRIMER

**Product Name:** SIM PANDA PRIMER

**Product Description:** Water based bituminous emulsion

**Application areas :** Vertical or horizontal grounds

**Application method:**

- \* the application place should be dry and clean, and should be removed from oil, gasoline & other chemical materials
- \* will be mixed with water ( 1:3 rate), and will be applied brush (400 gr/m<sup>2</sup>)
- \* if the consistence is much intense (thick) then please use hot water to make it thinner. (with % 10-15 rate)
- \* after application the color of concrete will be light brown
- \* after application clean brush or rolls with hot water
- \* After using primer close the cap of the bucket tightly.
- \* without opening the cap of the bucket you can keep it in stock for 1 year ( between +5 to +30 C)

SPECIFICATIONS	STANDARDS	UNIT	VALUES	TOLERANCE
Density	TS 132	gr/cm <sup>3</sup>	1,02	± 0,03
Vaporization waste	TS 132	%	65	± 5
Ash content of waste	TS 132	%	30	± 5
Water content	TS 132	%	55	± 5
Flammability	TS 132		Inflammable	
Drying period	TS 132	Hours	(Max.) 31	
Thermal Flow (100°C)	TS 132		No flow	
Flexibility (0°C)	TS 132		No cracking	
Direct flame test	TS 132		Scorching at place of application	
Water tightness	TS 132		Does not turn back into emulsion	